


IT'S
EASY
TO BE
CREATIVE

Profile LED

J

Data sheet

A recessed furniture LED profile designed for installation in a milled recess along the edge of furniture elements or built-in structures, such as shelves, panels, and countertops.



Assembly methods








Watch the video









LED Profiles

Length (mm): 1000, 2020, 3000

	WHITE (LACQUERED)	BLACK (ANODIZED)	INOX (ANODIZED)	SILVER (ANODIZED)	RAW
Profile colors					
1,0 m	10-0000-88	10-0000-93	10-0000-98	10-0001-03	10-0001-08
2,02 m	10-0000-89	10-0000-94	10-0000-99	10-0001-04	10-0001-09
3,0 m	10-0000-90	10-0000-95	10-0000-01	10-0001-05	10-0001-10
LED strip width (mm)	up to 12				

Covers (PMMA/PC)


Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK	LENS 15	LENS 30
BASIC								
								
1 m PMMA: 11-2213-10 1 m PC 2.0: 11-3533-10	1 m PC Fractal: 11-3213-10	1 m PMMA: 11-2212-10 1 m PC 2.0: 11-3532-10	1 m PMMA: 11-2211-10 1 m PC 2.0: 11-3531-10	1 m PMMA: 11-2216-10	1 m PC Fractal: 11-3211-10	1 m PMMA: 11-2217-10 1 m PC Fractal: 11-3347-10	1 m PMMA: 11-2060-10	1 m PMMA: 11-2080-10

End caps (plastic)

WITH HOLE							
WHITE		BLACK		INOX		SILVER / GRAY	
LEFT	RIGHT	LEFT	RIGHT	LEFT	RIGHT	LEFT	RIGHT
							
ABS 12-0000-63	ABS 12-0000-64	ABS 12-0000-65	ABS 12-0000-66	ABS 12-0000-67	ABS 12-0000-68	ABS lacq.12-1085-00 ABS 12-0000-69	ABS lacq.12-1185-00 ABS 12-0000-70

Accessories

Y M1 ASSEMBLY PROFILE	CONTACTLESS SWITCH
	
1 m: 10-0674-10 2,02 m: 10-0674-20 3 m: 10-0674-30	14-7052-00

Maximum dissipated power of LED light sources

for temperature profile 55° C	for temperature profile 65° C
24,2 W	32,1 W



www.lumines.com

