


IT'S
EASY
TO BE
CREATIVE

Profile LED

RUNO

Data sheet

A deep recessed LED profile designed for decorative floor lighting. Thanks to the sealing TERRA cover, which protects the LED strip against moisture ingress, it can also be used in areas exposed to humidity. The profile offers protection ratings of IP54 and impact resistance IK07.



Assembly methods



Watch the video





RUNO




LED Profiles

Length (mm): 1000, 2020, 3000



	WHITE (LACQUERED)	BLACK (LACQUERED)	SILVER (ANODIZED)
Profile colors			
1,0 m	10-0001-37	10-0755-10	10-0001-42
2,02 m	10-0001-38	10-0625-20	10-0001-43
3,0 m	10-0001-39	10-0755-30	10-0001-44
LED strip width (mm)	10		

Covers (PC)

Length (mm): 1000, 2020, 3000

MILKY
TERRA

1 m PC: 11-3041-10

End caps (aluminum and plastic)

WITH PUSH-HOLE			WITHOUT HOLE	WITH HOLE
WHITE	BLACK	SILVER / GRAY	SILVER (anodized)	SILVER (anodized)
				
ABS 12-0000-57	ABS 12-0000-71	ABS 12-0000-58 ABS lacq. 12-1105-01	ALU 12-2555-11	ALU 12-2555-10

Maximum dissipated power of LED light sources

for temperature profile	for temperature profile
55° C	65° C
19,1 W	25,8 W

Resistance and protection ratings

WATER RESISTANCE	STATIC LOAD	DYNAMIC RESISTANCE
IP54 protection class (according to PN-EN 60529 : 2003)	1,5 kN	IK07 protection rate for IP54 (according to PN-EN 50102 : 2001)



www.lumines.com

