


IT'S EASY TO BE CREATIVE

Profile LED

A

Data sheet

An LED profile designed for surface mounting with a wide range of applications. It is ideally suited for use as a decorative lighting element in furniture and interior finishes, as well as for suspended installations in architectural interiors.




A

Assembly methods









Bending methods














LED Profiles

Length (mm): 1000, 2020, 3000





	WHITE (LACQUERED)	BLACK (ANODIZED)	INOX (ANODIZED)	SILVER (ANODIZED)	RAW	GOLDEN (LACQUERED)
Profile colors						
1,0 m	10-0011-10	10-0012-10	10-0013-10	10-0014-10	10-0010-10	10-1666-10
2,02 m	10-0011-20	10-0012-20	10-0013-20	10-0014-20	10-0010-20	10-1666-20
3,0 m	10-0011-30	10-0012-30	10-0013-30	10-0014-30	10-0010-30	10-1666-30
LED strip width (mm)	up to 12					

Covers (PMMA/PC)

Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK	LENS 15	LENS 30	ASYMMETRIC LENS 45
BASIC									
									
1 m PMMA: 11-2213-10		1 m PMMA: 11-2212-10	1 m PMMA: 11-2211-10	1 m PMMA: 11-2216-10		1 m PMMA: 11-2217-10	1 m PMMA: 11-2060-10	1 m PMMA: 11-2080-10	
1 m PC 2.0: 11-3533-10	1 m PC Fractal: 11-3213-10	1 m PC 2.0: 11-3532-10	1 m PC 2.0: 11-3531-10		1 m PC Fractal: 11-3211-10	1 m PC Fractal: 11-3347-10			1 m PC: 11-3620-10
HIGH									
									
1 m PMMA: 11-2053-10		1 m PMMA: 11-2052-10	1 m PMMA: 11-2051-10	1 m PMMA: 11-2056-10		1 m PMMA: 11-2057-10			

End caps (aluminum and plastic)

WITH HOLE					WITHOUT HOLE				
WHITE	BLACK	INOX	SILVER / GRAY	GOLDEN	WHITE	BLACK	INOX	SILVER / GRAY	GOLDEN
BASIC									
									
ALU 12-0012-10			ALU 12-0015-10		ALU 12-0012-11			ALU 12-0015-11	
			ABS lacq. 12-0000-20					ABS lacq. 12-0000-34	
ABS 12-0011-00	ABS 12-0012-00	ABS 12-0013-00	ABS 12-0014-00	ABS 12-1719-00	ABS 12-0011-01	ABS 12-0012-01	ABS 12-0013-01	ABS 12-0014-01	ABS 12-1719-01
HIGH									
									
ALU 12-0022-10			ALU 12-0025-10		ALU 12-0022-11			ALU 12-0025-11	
			ABS lacq. 12-0000-33					ABS lacq. 12-0000-32	
ABS 12-0021-00	ABS 12-0022-00	ABS 12-0023-00	ABS 12-0024-00		ABS 12-0021-01	ABS 12-0022-01	ABS 12-0023-01	ABS 12-0024-01	

Accessories

	WHITE	BLACK	SILVER	GOLDEN			
A METAL MOUNTING CLIP							
	13-0631-02	13-0772-02	13-0110-02	13-1036-02			
	WHITE	BLACK	TRANSPARENT	GOLDEN			
A MINI PLASTIC MOUNTING CLIP							
	13-0021-00	13-0022-00	13-0023-00	13-0547-02			
	WHITE	BLACK	TRANSPARENT	A HIGH PLASTIC MOUNTING CLIP	WHITE	BLACK	TRANSPARENT
A PLASTIC MOUNTING CLIP							
	13-0011-00	13-0012-00	13-0013-00		13-0031-00	13-0032-00	13-0033-00

Accessories

	WHITE	BLACK	SILVER				
PENDANTS							
	14-2075-00	14-2076-00	14-2011-02				
	TRANSPARENT	BLACK	HINGE		CONTACTLESS SWITCH		
CABLE Ø 5 mm HOLDER							
	14-7067-00	14-7067-02		14-6045-00		14-7052-00	

Maximum dissipated power of LED light sources

for temperature profile 55° C	for temperature profile 65° C
17,0 W	22,2 W



www.lumines.com

