


IT'S
EASY
TO BE
CREATIVE

Profile LED

B

Data sheet

An LED profile designed for recessed installation in milled surface openings. One of the most minimalist and contemporary designs in the range. The minimum required recess depth is just 9 mm.



Assembly methods








Watch the video










LED Profiles

Length (mm): 1000, 2020, 3000

	WHITE (LACQUERED)	BLACK (ANODIZED)	INOX (ANODIZED)	SILVER (ANODIZED)	RAW	GOLDEN (LACQUERED)
Profile colors						
1,0 m	10-0021-10	10-0022-10	10-0023-10	10-0024-10	10-0020-10	10-1676-10
2,02 m	10-0021-20	10-0022-20	10-0023-20	10-0024-20	10-0020-20	10-1676-20
3,0 m	10-0021-30	10-0022-30	10-0023-30	10-0024-30	10-0020-30	10-1676-30
LED strip width (mm)	up to 12					

Covers (PMMA/PC)

Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK	LENS 15	LENS 30
BASIC								
								
1 m PMMA: 11-2213-10 1 m PC 2.0: 11-3533-10	1 m PC Fractal: 11-3213-10	1 m PMMA: 11-2212-10 1 m PC 2.0: 11-3532-10	1 m PMMA: 11-2211-10 1 m PC 2.0: 11-3531-10	1 m PMMA: 11-2216-10	1 m PC Fractal: 11-3211-10	1 m PMMA: 11-2217-10 1 m PC Fractal: 11-3347-10	1 m PMMA: 11-2060-10	1 m PMMA: 11-2080-10
ASYMMETRIC LENS 45								
BASIC								
								
1 m PC: 11-3620-10								

End caps (aluminum and plastic)

FLAT FINISH					ROUND FINISH				
WHITE	BLACK	INOX	SILVER / GRAY	GOLDEN	WHITE	BLACK	INOX	SILVER / GRAY	GOLDEN
									
ABS lacq. 12-0000-35					ALU 12-0032-10				
ABS 12-0151-00	ABS 12-0152-00	ABS 12-0153-00	ABS 12-0154-00	ABS 12-1729-00	ABS 12-0031-00	ABS 12-0032-00	ABS 12-0033-00	ABS 12-0034-00	ABS 12-1909-00

Accessories

CONTACTLESS SWITCH



14-7052-00



www.lumines.com

