


IT'S EASY TO BE CREATIVE

Profile LED

C

Data sheet

A surface-mounted corner LED profile with a 45° LED strip inclination angle. A groove on the rear side of the profile allows it to be pressed tightly into corners (furniture or walls) even in the presence of surface irregularities. It also enables the concealment of a small-diameter cable.



Assembly methods









Watch the video



C









LED Profiles

Length (mm): 1000, 2020, 3000



	WHITE (LACQUERED)	BLACK (ANODIZED)	INOX (ANODIZED)	SILVER (ANODIZED)	RAW	GOLDEN (LACQUERED)
Profile colors						
1,0 m	10-0031-10	10-0032-10	10-0033-10	10-0034-10	10-0030-10	10-1686-10
2,02 m	10-0031-20	10-0032-20	10-0033-20	10-0034-20	10-0030-20	10-1686-20
3,0 m	10-0031-30	10-0032-30	10-0033-30	10-0034-30	10-0030-30	10-1686-30
LED strip width (mm)	up to 12					

Covers (PMMA/PC)


Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK	LENS 15	LENS 30
BASIC								
								
1 m PMMA: 11-2213-10		1 m PMMA: 11-2212-10	1 m PMMA: 11-2211-10	1 m PMMA: 11-2216-10		1 m PMMA: 11-2217-10	1 m PMMA: 11-2060-10	1 m PMMA: 11-2080-10
1 m PC 2.0: 11-3533-10	1 m PC Fractal: 11-3213-10	1 m PC 2.0: 11-3532-10	1 m PC 2.0: 11-3531-10		1 m PC Fractal: 11-3211-10	1 m PC Fractal: 11-3347-10		

End caps (aluminum and plastic)

WITH HOLE					WITHOUT HOLE				
WHITE	BLACK	INOX	SILVER / GRAY	GOLDEN	WHITE	BLACK	INOX	SILVER / GRAY	GOLDEN
									
	ALU 12-0042-10		ALU 12-0045-10			ALU 12-0042-11		ALU 12-0045-11	
			ABS lacq. 12-0000-38					ABS lacq. 12-0000-37	
ABS 12-0041-00	ABS 12-0042-00	ABS 12-0043-00	ABS 12-0044-00	ABS 12-1739-00	ABS 12-0041-01	ABS 12-0042-01	ABS 12-0043-01	ABS 12-0044-01	ABS 12-1739-01

Accessories

	WHITE	BLACK	SILVER	GOLDEN
CH METAL MOUNTING CLIP				
	13-0641-02	13-0782-02	13-0120-02	13-1046-02
CH PLASTIC MOUNTING CLIP				
	13-0041-00	13-0042-00	13-0043-00	13-0557-02
PENDANTS				
	14-2075-00	14-2076-00	14-2011-02	
CABLE Ø 5 mm HOLDER			HINGE	
	14-7067-00	14-7067-02		CONTACTLESS SWITCH
				
				14-7052-00

Maximum dissipated power of LED light sources

for temperature profile 55° C	for temperature profile 65° C
23,0 W	31,0 W



www.lumines.com

