


IT'S
EASY
TO BE
CREATIVE

Profile LED

G

Data sheet

A recessed LED profile designed for lighting applications in kitchens and retail spaces, suitable for installation inside cabinets, countertops, and stairs.



Assembly methods









Watch the video



G









LED Profiles

Length (mm): 1000, 2020, 3000

	WHITE (LACQUERED)	BLACK (ANODIZED)	INOX (ANODIZED)	SILVER (ANODIZED)	RAW	GOLDEN (LACQUERED)
Profile colors						
1,0 m	10-0071-10	10-0072-10	10-0073-10	10-0074-10	10-0070-10	10-1706-10
2,02 m	10-0071-20	10-0072-20	10-0073-20	10-0074-20	10-0070-20	10-1706-20
3,0 m	10-0071-30	10-0072-30	10-0073-30	10-0074-30	10-0070-30	10-1706-30
LED strip width (mm)	up to 12					

Covers (PMMA/PC)


Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK	LENS 15	LENS 30
BASIC								
								
1 m PMMA: 11-2213-10 1 m PC 2.0: 11-3533-10	1 m PC Fractal: 11-3213-10	1 m PMMA: 11-2212-10 1 m PC 2.0: 11-3532-10	1 m PMMA: 11-2211-10 1 m PC 2.0: 11-3531-10	1 m PMMA: 11-2216-10		1 m PMMA: 11-2217-10 1 m PC Fractal: 11-3347-10	1 m PMMA: 11-2060-10	1 m PMMA: 11-2080-10

End caps (aluminum and plastic)

WITH HOLE					
WHITE	BLACK	INOX	SILVER / GRAY	GOLDEN	
					
	ALU 12-0072-10		ALU 12-0075-10		
ABS 12-0071-00	ABS 12-0072-00	ABS 12-0073-00	ABS lacq. 12-0000-49 ABS 12-0074-00	ABS 12-1759-00	

Accessories

Y M1 ASSEMBLY PROFILE	CONTACTLESS SWITCH
	
1 m: 10-0674-10 2,02 m: 10-0674-20 3 m: 10-0674-30	14-7052-00

Maximum dissipated power of LED light sources

for temperature profile 55° C	for temperature profile 65° C
24,4 W	32,5 W



www.lumines.com

