


IT'S
EASY
TO BE
CREATIVE

Profile LED

TERRA

Data sheet

A recessed LED profile designed for decorative floor lighting. Thanks to the sealing TERRA cover, which protects the LED strip against moisture ingress, it can also be used in areas exposed to humidity. The profile offers protection ratings of IP54 and impact resistance IK07.



TERRA

Assembly methods



Watch the video






TERRA

TERRA


LED Profiles

Length (mm): 1000, 2020, 3000

	WHITE (LACQUERED)	BLACK (LACQUERED)	SILVER (ANODIZED)	GOLDEN (LACQUERED)
Profile colors				
1,0 m	10-0151-10	10-0000-50	10-0154-10	10-1716-10
2,02 m	10-0151-20	10-0000-51	10-0154-20	10-1716-20
3,0 m	10-0151-30	10-0155-30	10-0154-30	10-1716-30
LED strip width (mm)	10			

Covers (PC)

Length (mm): 1000, 2020, 3000

MILKY
TERRA

1 m PC: 11-3041-10

End caps (aluminum and plastic)

WITH HOLE				WITHOUT HOLE			
WHITE	BLACK	SILVER / GRAY	GOLDEN	WHITE	BLACK	SILVER / GRAY	GOLDEN
							
		ALU 12-0145-10 ABS lacq. 12-0145-00				ALU 12-0145-11 ABS lacq. 12-0145-01	
ABS 12-0141-00	ABS 12-0142-00	ABS 12-0144-00	ABS 12-1769-00	ABS 12-0141-01	ABS 12-0142-01	ABS 12-0144-01	ABS 12-1769-01

Maximum dissipated power of LED light sources

for temperature profile 55° C		for temperature profile 65° C	
WITH COVER	WITHOUT COVER	WITH COVER	WITHOUT COVER
17,0 W	17,7 W	23,5 W	24,0 W

Resistance and protection ratings

WATER RESISTANCE	STATIC LOAD	DYNAMIC RESISTANCE
IP54 protection class (according to PN-EN 60529 : 2003)	1,5 kN	IK07 protection rate for IP54 (according to PN-EN 50102 : 2001)



www.lumines.com

