


IT'S
EASY
TO BE
CREATIVE

Profile LED


COSMO

Data sheet

A round, adjustable LED profile for targeted illumination; it can also be used as a closet rod. When used with the COSMO M1 mounting profile, the beam direction can be adjusted without removing the end caps, and the profile can also be rotated along its own axis via indexed, step-by-step adjustment within the mounting bracket.



Assembly methods



Watch the video



LED Profiles

Length (mm): 1000, 2020, 3000

	WHITE (LACQUERED)	BLACK (ANODIZED)	INOX (ANODIZED)	SILVER (ANODIZED)	RAW
Profile colors					
1,0 m	10-0171-10	10-0172-10	10-0173-10	10-0174-10	10-0170-10
2,02 m	10-0171-20	10-0172-20	10-0173-20	10-0174-20	10-0170-20
3,0 m	10-0171-30	10-0172-30	10-0173-30	10-0174-30	10-0170-30
LED strip width (mm)	up to 12				

Covers (PMMA/PC)

Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK	LENS 15	LENS 30
BASIC								
1 m PMMA: 11-2213-10 1 m PC 2.0: 11-3533-10	1 m PC Fractal: 11-3213-10	1 m PMMA: 11-2212-10 1 m PC 2.0: 11-3532-10	1 m PMMA: 11-2211-10 1 m PC 2.0: 11-3531-10	1 m PMMA: 11-2216-10	1 m PC Fractal: 11-3211-10	1 m PMMA: 11-2217-10 1 m PC Fractal: 11-3347-10	1 m PMMA: 11-2060-10	1 m PMMA: 11-2080-10

End caps (aluminum and plastic)

BLACK	SILVER	BLACK	SILVER	WHITE	BLACK	INOX	SILVER / GRAY
WITH HOLE		WITHOUT HOLE		WITH PUSH-HOLE			
ALU 12-0172-10	ALU 12-0175-10	ALU 12-0172-11	ALU 12-0175-11	ABS 12-0921-01	ABS 12-0922-01	ABS 12-0923-01	ABS lacq.12-0925-01 ABS 12-0924-01
ADJUSTMENT END CAP WITH HOLE		ADJUSTMENT END CAP WITHOUT HOLE		ADJUSTING RING			
ALU 12-0182-10	ALU 12-0185-10	ALU 12-0182-11	ALU 12-0185-11	ALU 14-5042-02		ALU 14-5042-04	

Accessories

	WHITE	BLACK	SILVER	
COSMO METAL MOUNTING CLIP				
	13-0681-02	13-0822-02	13-0130-02	
HINGE		HINGE JOINT BASE		ARTICULATED SYSTEM – SET
	14-6045-00		14-6044-02	 14-6044-01
HIGH COLLAR – FULL END		HIGH COLLAR – WITH HOLE		LOW COLLAR – FULL END
	14-5047-01		14-5047-02	 14-5043-01
BASIC COLLAR Ø 25 MM CHROME		METRO ASSEMBLY PROFILE		COSMO M1 ASSEMBLY PROFILE
	14-5043-00		1 m: 10-0294-10 2,02 m: 10-0294-20 3 m: 10-0294-30	 1 m: 10-0164-10 2,02 m: 10-0164-20 3 m: 10-0164-30
ANGULAR CONNECTOR 120°		ANGULAR CONNECTOR 90°		STRAIGHT CONNECTOR
	14-3036-01		14-3030-01	 14-3032-02

Maximum dissipated power of LED light sources

for temperature profile 55° C	for temperature profile 65° C
21,0 W	28,0 W



www.lumines.com

