


IT'S
EASY
TO BE
CREATIVE

Profile LED


DILED A

Data sheet

A surface-mounted profile for room lighting using two LED strips, suitable for surface-mounted or suspended installation, ideal for custom single or continuous linear luminaires in various shapes using dedicated connectors, with optional raster cover compatibility to improve visual comfort.



Assembly methods



Bending methods

VERTICAL BENDING





Watch the video



DILED A











LED Profiles

Length (mm): 1000, 2020, 3000

	WHITE (LACQUERED)	BLACK (LACQUERED)	SILVER (ANODIZED)
Profile colors			
1,0 m	10-0181-10	10-0185-10	10-0184-10
2,02 m	10-0181-20	10-0185-20	10-0184-20
3,0 m	10-0181-30	10-0185-30	10-0184-30
LED strip width (mm)	2 x 12		

Covers (PMMA/PC/SILICONE DOW CORNING)

Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK	SILVER	BLACK
DOUBLE							RASTER DOUBLE	
								
1 m PMMA: 11-2073-10 1 m PC 2.0: 11-3733-10	1 m PC Fractal: 11-3373-10	1 m PMMA: 11-2072-10 1 m PC 2.0: 11-3722-10	1 m PMMA: 11-2071-10 1 m PC 2.0: 11-3701-10	1 m PMMA: 11-2076-10	1 m PC Fractal: 11-3371-10	1 m PMMA: 11-2077-10 1 m PC Fractal: 11-3470-10	1 m: 14-0000-48	1 m: 14-2028-82
OPAL								
TALL		DOUBLE FLEX						
								
1 m PC Fractal: 11-3521-10	SILICONE DOW CORNING 1 m: 11-4641-10							

End caps (aluminum and plastic)

WITH HOLE			WITHOUT HOLE		
WHITE	BLACK	SILVER	WHITE	BLACK	SILVER
					
ALU 12-0191-10	ALU 12-0192-10	ALU 12-0195-10	ALU 12-0191-11	ALU 12-0192-11	ALU 12-0195-11
WITH PUSH-HOLE					
WHITE	BLACK	SILVER			
					
ABS 12-0931-01	ABS 12-0932-01	ABS 12-0934-01 ABS lacq. 12-0935-01			
DILED A + TALL COVER					
WITH HOLE			WITHOUT HOLE		
WHITE	BLACK	SILVER	WHITE	BLACK	SILVER
					
ALU lacq. 12-2021-10	ALU lacq. 12-2022-10	ALU 12-2025-10	ALU lacq. 12-2021-11	ALU lacq. 12-2022-11	ALU 12-2025-11

Accessories

SLT METAL MOUNTING CLIP	CONTACTLESS SWITCH	HINGE JOINT BASE	HINGE	ARTICULATED SYSTEM – SET	
					
13-0000-02	14-7052-00	14-6044-02	14-6045-00	14-6044-01	
STRAIGHT CONNECTOR	90° ANGULAR CONNECTOR	90° ANGULAR TRANSVERSE CONNECTOR	120° ANGULAR CONNECTOR	135° ANGULAR CONNECTOR	3 x 120° ANGULAR CONNECTOR
					
14-3032-02	14-3030-01	14-3038-01	14-3036-01	14-3028-67	14-3028-65
PENDANTS			CABLE Ø 5 mm HOLDER		
WHITE	BLACK	SILVER	TRANSPARENT	BLACK	
					
14-2075-00	14-2076-00	14-2011-02	14-7067-00	14-7067-02	
CONNECTOR TYPE L		CONNECTOR TYPE T		CONNECTOR TYPE X	
WHITE (LACQUERED)	BLACK (LACQUERED)	WHITE (LACQUERED)	BLACK (LACQUERED)	WHITE (LACQUERED)	BLACK (LACQUERED)
					
14-2029-48	14-2029-57	14-2029-49	14-2029-58	14-2029-50	14-2029-59

Maximum dissipated power of LED light sources

for temperature profile	for temperature profile
55° C	65° C
29,4 W	39,2 W



www.lumines.com

