


IT'S
EASY
TO BE
CREATIVE

Profile LED


inDILEDA

Data sheet

A recessed architectural profile for ceiling and wall applications, installed in a milled opening and accommodating two LED strips, ideal for custom LED luminaires and continuous linear systems in various shapes using dedicated connectors, with optional raster cover compatibility to improve visual comfort.





Assembly methods



inDILEDA










LED Profiles

Length (mm): 1000, 2020, 3000

	WHITE (LACQUERED)	BLACK (LACQUERED)	SILVER (ANODIZED)
Profile colors			
1,0 m	10-0201-10	10-0205-10	10-0204-10
2,02 m	10-0201-20	10-0205-20	10-0204-20
3,0 m	10-0201-30	10-0205-30	10-0204-30
LED strip width (mm)	2 x 12		

Covers (PMMA/PC)


Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK	SILVER	BLACK
DOUBLE						RASTER DOUBLE		
								
1 m PMMA: 11-2073-10 1 m PC 2.0: 11-3733-10	1 m PC Fractal: 11-3373-10	1 m PMMA: 11-2072-10 1 m PC 2.0: 11-3722-10	1 m PMMA: 11-2071-10 1 m PC 2.0: 11-3701-10	1 m PMMA: 11-2076-10	1 m PC Fractal: 11-3371-10	1 m PMMA: 11-2077-10 1 m PC Fractal: 11-3470-10	1 m: 14-0000-48	1 m: 14-2028-82

End caps (aluminum and plastic)

WITH HOLE		
WHITE	BLACK	SILVER / GRAY
		
ALU 12-0391-10 ABS 12-0961-00	ALU 12-0000-09	ALU 12-0395-10 ABS lacq. 12-0965-00 ABS 12-0964-00

Accessories

STRAIGHT CONNECTOR	90° ANGULAR CONNECTOR	90° ANGULAR TRANSVERSE CONNECTOR	120° ANGULAR CONNECTOR	135° ANGULAR CONNECTOR	3 x 120° ANGULAR CONNECTOR
					
14-3032-02	14-3030-01	14-3038-01	14-3036-01	14-3028-67	14-3028-65
MOUNTING SPRING	CONTACTLESS SWITCH	SLT METAL MOUNTING CLIP			
					
14-5001-00	14-7052-00	13-0000-02			

Maximum dissipated power of LED light sources

for temperature profile	for temperature profile
55° C	65° C
30,8 W	40,6 W



www.lumines.com

