


IT'S
EASY
TO BE
CREATIVE

Profile LED

inSILEDA

Data sheet

A recessed architectural profile designed for ceiling and wall applications, installed in a milled opening. It allows two LED strips to be mounted in parallel. The profile is an excellent base for building custom LED luminaires, including single fixtures and continuous linear lighting systems in various shapes using dedicated connectors.



Assembly methods



Watch the video




inSILEDA

inSILEDA







LED Profiles

Length (mm): 1000, 2020, 3000

	WHITE (LACQUERED)	BLACK (LACQUERED)	SILVER (ANODIZED)
Profile colors			
1,0 m	10-0221-10	10-0225-10	10-0224-10
2,02 m	10-0221-20	10-0225-20	10-0224-20
3,0 m	10-0221-30	10-0225-30	10-0224-30
LED strip width (mm)	2 x 12		

Covers (PMMA/PC)



Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK
DOUBLE						
						
1 m PMMA: 11-2073-10 1 m PC 2.0: 11-3733-10	1 m PC Fractal: 11-3373-10	1 m PMMA: 11-2072-10 1 m PC 2.0: 11-3722-10	1 m PMMA: 11-2071-10 1 m PC 2.0: 11-3701-10	1 m PMMA: 11-2076-10	1 m PC Fractal: 11-3371-10	1 m PMMA: 11-2077-10 1 m PC Fractal: 11-3470-10

End caps (aluminum and plastic)

WITH HOLE		
WHITE	BLACK	SILVER / GRAY
		
ALU 12-0411-10 ABS 12-0971-00	ALU 12-0000-11 ABS 12-1172-00	ALU 12-0415-10 ABS lacq. 12-0975-00 ABS 12-0974-00

Accessories

STRAIGHT CONNECTOR	90° ANGULAR CONNECTOR	ANGULAR TRANSVERSE CONNECTOR	120° ANGULAR CONNECTOR	135° ANGULAR CONNECTOR	3 x 120° ANGULAR CONNECTOR
					
14-3032-02	14-3030-01	14-3038-01	14-3036-01	14-3028-67	14-3028-65
MOUNTING SPRING	CONTACTLESS SWITCH	SLT METAL MOUNTING CLIP			
					
14-5001-00	14-7052-00	13-0000-02			

Maximum dissipated power of LED light sources

for temperature profile 55° C	for temperature profile 65° C
28,0 W	37,8 W



www.lumines.com

