


IT'S
EASY
TO BE
CREATIVE

Profile LED

SILEDA

Data sheet

A surface-mounted profile for room lighting using two LED strips; it can be installed surface-mounted or suspended and serves as an excellent base for custom LED luminaires, including single fixtures and continuous linear lighting systems in various shapes using dedicated connectors.



Assembly methods





SILED A

LED Profiles







Length (mm): 1000, 2020, 3000

SILED A

	WHITE (LACQUERED)	BLACK (LACQUERED)	SILVER (ANODIZED)
Profile colors			
1,0 m	10-0331-10	10-0335-10	10-0334-10
2,02 m	10-0331-20	10-0335-20	10-0334-20
3,0 m	10-0331-30	10-0335-30	10-0334-30
LED strip width (mm)	2 x 12		

Covers (PMMA/PC)


Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK	OPAL
DOUBLE						TALL	
							
1 m PMMA: 11-2073-10 1 m PC 2.0: 11-3733-10	1 m PC Fractal: 11-3373-10	1 m PMMA: 11-2072-10 1 m PC 2.0: 11-3722-10	1 m PMMA: 11-2071-10 1 m PC 2.0: 11-3701-10	1 m PMMA: 11-2076-10	1 m PC Fractal: 11-3371-10	1 m PMMA: 11-2077-10 1 m PC Fractal: 11-3470-10	1 m PC Fractal: 11-3521-10

End caps (aluminum and plastic)

WITH HOLE			WITHOUT HOLE		
WHITE	BLACK	SILVER / GRAY	WHITE	BLACK	SILVER / GRAY
					
ALU 12-0641-10	ALU 12-0000-21	ALU 12-0645-10	ALU 12-0641-11	ALU 12-0000-19	ALU 12-0645-11
WITH PUSH-HOLE					
WHITE	BLACK	SILVER / GRAY			
					
ABS 12-1001-01	ABS 12-1002-01	ABS lacq. 12-1005-01 ABS 12-1004-01			
SILED A + TALL COVER					
WITH HOLE			WITHOUT HOLE		
WHITE	BLACK	SILVER (ANODIZED)	WHITE	BLACK	SILVER (ANODIZED)
					
ALU lacq. 12-2011-10	ALU lacq. 12-2012-10	ALU 12-2015-10	ALU lacq. 12-2011-11	ALU lacq. 12-2012-11	ALU 12-2015-11

Accessories

SLT METAL MOUNTING CLIP	CONTACTLESS SWITCH	HINGE JOINT BASE	HINGE	ARTICULATED SYSTEM – SET	
					
13-0000-02	14-7052-00	14-6044-02	14-6045-00	14-6044-01	
STRAIGHT CONNECTOR	90° ANGULAR CONNECTOR	ANGULAR TRANSVERSE CONNECTOR	120° ANGULAR CONNECTOR	135° ANGULAR CONNECTOR	3 x 120° ANGULAR CONNECTOR
					
14-3032-02	14-3030-01	14-3038-01	14-3036-01	14-3028-67	14-3028-65
PENDANTS			CABLE Ø 5 mm HOLDER		
WHITE	BLACK	SILVER	TRANSPARENT	BLACK	
					
14-2075-00	14-2076-00	14-2011-02	14-7067-00	14-7067-02	

Maximum dissipated power of LED light sources

for temperature profile	for temperature profile
55° C	65° C
26,6 W	36,4 W



www.lumines.com

