


IT'S EASY TO BE CREATIVE

Profile LED


W

Data sheet

A recessed LED profile designed for installation in lightweight constructions using mounting springs, ensuring quick and secure installation with clean integration into ceilings or walls without visible fixtures. It is suitable for creating continuous lines of light or subtle accent illumination in architectural interiors.



Assembly methods






Watch the video



W








LED Profiles

Length (mm): 1000, 2020, 3000



	WHITE (LACQUERED)	BLACK (ANODIZED)	INOX (ANODIZED)	SILVER (ANODIZED)	RAW
Profile colors					
1,0 m	10-0701-10	10-0702-10	10-0703-10	10-0704-10	10-0700-10
2,02 m	10-0701-20	10-0702-20	10-0703-20	10-0704-20	10-0700-20
3,0 m	10-0701-30	10-0702-30	10-0703-30	10-0704-30	10-0700-30
LED strip width (mm)	up to 12				

Covers (PMMA/PC)


Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK	LENS 15	LENS 30
BASIC								
								
1 m PMMA: 11-2213-10 1 m PC 2.0: 11-3533-10	1 m PC Fractal: 11-3213-10	1 m PMMA: 11-2212-10 1 m PC 2.0: 11-3532-10	1 m PMMA: 11-2211-10 1 m PC 2.0: 11-3531-10	1 m PMMA: 11-2216-10	1 m PC Fractal: 11-3211-10	1 m PMMA: 11-2217-10 1 m PC Fractal: 11-3347-10	1 m PMMA: 11-2060-10	1 m PMMA: 11-2080-10

End caps (aluminum and plastic)

WITH A HOLE			
WHITE	BLACK	INOX	SILVER / GRAY
			
ABS 12-0071-00	ALU 12-0072-10 ABS 12-0072-00	ABS 12-0073-00	ALU 12-0075-10 ABS lacq. 12-0000-49 ABS 12-0074-00

Accessories

STRAIGHT CONNECTOR	90° ANGULAR CONNECTOR	ANGULAR TRANSVERSE CONNECTOR	120° ANGULAR CONNECTOR	135° ANGULAR CONNECTOR	3 x 120° ANGULAR CONNECTOR
					
14-3032-02	14-3030-01	14-3038-01	14-3036-01	14-3028-67	14-3028-65
MOUNTING SPRING	CONTACTLESS SWITCH	Y M1 ASSEMBLY PROFILE			
					
14-5001-00	14-7052-00	1 m: 10-0674-10 2,02 m: 10-0674-20 3 m: 10-0674-30			

Maximum dissipated power of LED light sources

for temperature profile	for temperature profile
55° C	65° C
23,8 W	32,0 W



www.lumines.com

