


IT'S
EASY
TO BE
CREATIVE

Profile LED

GEMI

Data sheet

A wide recessed LED profile for installation in milled openings, designed to accommodate two parallel LED strips. Ideal for creating a broader, more uniform line of decorative light in furniture and gypsum-board applications.





Assembly methods



GEMI







LED Profiles

Length (mm): 1000, 2020, 3000

	WHITE (LACQUERED)	BLACK (ANODIZED)	SILVER (ANODIZED)	RAW
Profile colors				
1,0 m	10-0991-10	10-1002-10	10-1014-10	10-1020-10
2,02 m	10-0991-20	10-1002-20	10-1014-20	10-1020-20
3,0 m	10-0991-30	10-1002-30	10-1014-30	10-1020-30
LED strip width (mm)	2 x 10			

Covers (PMMA/PC)

Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK
DOUBLE						
						
1 m PMMA: 11-2073-10 1 m PC 2.0: 11-3733-10	1 m PC Fractal: 11-3373-10	1 m PMMA: 11-2072-10 1 m PC 2.0: 11-3722-10	1 m PMMA: 11-2071-10 1 m PC 2.0: 11-3701-10	1 m PMMA: 11-2076-10	1 m PC Fractal: 11-3371-10	1 m PMMA: 11-2077-10 1 m PC Fractal: 11-3470-10

End caps (plastic)

WITH HOLE			
WHITE	BLACK	SILVER	GRAY
			
ABS 12-1051-00	ABS 12-1052-00	ABS lacq. 12-1055-01	ABS 12-1054-00

Accessories

CONTACTLESS SWITCH



14-7052-00

Maximum dissipated power of LED light sources

for temperature profile	for temperature profile
55° C	65° C
22,9 W	30,7 W



www.lumines.com

