


IT'S EASY TO BE CREATIVE

Profile LED

U

Data sheet

Recessed LED profile with a height adapted to standard gypsum plasterboard or 12 mm furniture panels. It allows for quick recessed installation without the need for finishing with joint compound.



Assembly methods



U

U







LED Profiles

Length (mm): 1000, 2020, 3000

	WHITE (LACQUERED)	BLACK (ANODIZED)	SILVER (ANODIZED)	RAW
Profile colors				
1,0 m	10-1031-10	10-1042-10	10-1054-10	10-1060-10
2,02 m	10-1031-20	10-1042-20	10-1054-20	10-1060-20
3,0 m	10-1031-30	10-1042-30	10-1054-30	10-1060-30
LED strip width (mm)	up to 12			

Covers (PMMA/PC)

Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK	LENS 15	LENS 30
BASIC								
								
1 m PMMA: 11-2213-10 1 m PC 2.0: 11-3533-10	1 m PC Fractal: 11-3213-10	1 m PMMA: 11-2212-10 1 m PC 2.0: 11-3532-10	1 m PMMA: 11-2211-10 1 m PC 2.0: 11-3531-10	1 m PMMA: 11-2216-10	1 m PC Fractal: 11-3211-10	1 m PMMA: 11-2217-10 1 m PC Fractal: 11-3347-10	1 m PMMA: 11-2060-10	1 m PMMA: 11-2080-10

End caps (plastic)

WITH HOLE			
WHITE	BLACK	SILVER	GRAY
			
ABS 12-1061-00	ABS 12-1062-00	ABS lacq. 12-1065-01	ABS 12-1064-00

Accessories

CONTACTLESS SWITCH

14-7052-00

Maximum dissipated power of LED light sources

for temperature profile 55° C	for temperature profile 65° C
24,5 W	32,8 W



www.lumines.com

