


IT'S
EASY
TO BE
CREATIVE

LED System

STRADA

Data sheet

A hermetic LED system resistant to loads generated by vehicle traffic of up to 12 tonnes per axle. Intended for installation in driveways, pavements, and other areas requiring high-strength, IP68-rated linear lighting, with IK10 impact resistance.



Assembly methods



Watch the video




STRADA



LED Profiles

Length (mm): 1000, 2020, 3000

	SILVER (ANODIZED, SEALFLOW® SEALED)	SILVER (ANODIZED)
Profile colors		
1,0 m	10-1514-10	10-1094-10
2,02 m	10-1514-20	10-1094-20
3,0 m	10-1514-30	10-1094-30
LED strip width (mm)	up to 12	

Covers (PC)


Length (mm): 1000, 2020, 3000

MILKY
SOLID

1 m PC: 11-3221-10

Assembly profiles

Length (mm): 1000, 2020, 3000

	STRADA M1	STRADA M3
Profile colors	SILVER (ANODIZED) 	SILVER (ANODIZED) 
1,0 m	10-1104-10	10-1114-10
2,02 m	10-1104-20	10-1114-20
3,0 m	10-1104-30	10-1114-30

End caps (aluminum)

STRADA	STRADA M1	STRADA M3	STRADA M3-M1	STRADA	STRADA M1	STRADA M3	STRADA M3-M1
WITH HOLE				WITHOUT HOLE			
SILVER	SILVER	SILVER	SILVER	SILVER	SILVER	SILVER	SILVER
							
12-1265-10	12-1295-10	12-1285-10	12-1305-10	12-1255-11	12-1295-11	12-1285-11	12-1245-11
STRADA							
WITH GLAND							
SILVER							
							
12-2335-11							

Accessories

STRADA METAL MOUNTING CLIP	STRAIGHT CONNECTOR	TAPO END CAP	LUMINES SILICONE FOR LED PROFILES		
			GRAY		BLACK
13-0220-02	12-1295-10	12-1290-01			
			300 ml: 14-4028-70	20 ml: 14-4028-69	20 ml: 14-4028-71



www.lumines.com

