


IT'S
EASY
TO BE
CREATIVE

Profile LED

SLIMO

Data sheet

A compact LED profile suitable for suspended installation or surface mounting. Its recessed cover reduces glare (UGR) and narrows the light distribution angle, improving visual comfort.



Assembly methods





SLIMO










LED Profiles

Length (mm): 1000, 2020, 3000





	WHITE (LACQUERED)	BLACK (LACQUERED)	SILVER (ANODIZED)
Profile colors			
1,0 m	10-1171-10	10-1175-10	10-1174-10
2,02 m	10-1171-20	10-1175-20	10-1174-20
3,0 m	10-1171-30	10-1175-30	10-1174-30
LED strip width (mm)	up to 14,6		

Covers (PMMA/PC)

Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK
BASIC						
						
1 m PMMA: 11-2213-10 1 m PC 2.0: 11-3533-10	1 m PC Fractal: 11-3213-10	1 m PMMA: 11-2212-10 1 m PC 2.0: 11-3532-10	1 m PMMA: 11-2211-10 1 m PC 2.0: 11-3531-10	1 m PMMA: 11-2216-10	1 m PC Fractal: 11-3211-10	1 m PMMA: 11-2217-10 1 m PC Fractal: 11-3347-10

End caps (aluminum and plastic)

WITH HOLE			WITHOUT HOLE		
WHITE	BLACK	SILVER	WHITE	BLACK	SILVER
					
ALU lacq. 12-1471-10	ALU lacq. 12-1472-10	ALU anod. 12-1465-11	ALU lacq. 12-1461-11	ALU lacq. 12-1462-11	ALU anod. 12-1475-10
WITH PUSH-HOLE					
WHITE	BLACK	SILVER / GRAY			
					
ABS 12-1381-01	ABS 12-1382-01	ABS lacq. 12-1385-01 ABS 12-1384-01			

Accessories

SLT METAL MOUNTING CLIP	PENDANTS			CABLE Ø 5 mm HOLDER	
	WHITE	BLACK	SILVER	TRANSPARENT	BLACK
					
13-0000-02	14-2075-00	14-2076-00	14-2011-02	14-7067-00	14-7067-02
STRAIGHT CONNECTOR	90° ANGULAR CONNECTOR	ANGULAR TRANSVERSE CONNECTOR	120° ANGULAR CONNECTOR	135° ANGULAR CONNECTOR	3 x 120° ANGULAR CONNECTOR
					
14-3032-02	14-3030-01	14-3038-01	14-3036-01	14-3028-67	14-3028-65



www.lumines.com

