


IT'S EASY TO BE CREATIVE

Profile LED

CANTO

Data sheet

An external-corner LED profile available in two versions. The perforated version is designed for under-tile applications, featuring perforated triangular flanges that ensure even adhesive distribution and stable installation, making it suitable for accent lighting. The non-perforated version is intended for installation in plasterboard (drywall) systems.








Assembly methods



CANTO








LED Profiles

Length (mm): 1000, 2020, 3000







	WHITE (LACQUERED)	BLACK (LACQUERED)	SILVER (ANODIZED)	RAW
Colors of profiles without perforations				
1,0 m	10-1491-10	10-1495-10	10-1494-10	10-1490-10
2,02 m	10-1491-20	10-1495-20	10-1494-20	10-1490-20
3,0 m	10-1491-30	10-1495-30	10-1494-30	10-1490-30
Colors of profiles with perforations				
1,0 m	10-1541-10	10-1545-10	10-1544-10	10-1540-10
2,02 m	10-1541-20	10-1545-20	10-1544-20	10-1540-20
3,0 m	10-1541-30	10-1545-30	10-1544-30	10-1540-30
LED strip width (mm)	up to 12			

Covers (PMMA/PC)

Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK
BASIC						
						
1 m PMMA: 11-2213-10 1 m PC 2.0: 11-3533-10	1 m PC Fractal: 11-3213-10	1 m PMMA: 11-2212-10 1 m PC 2.0: 11-3532-10	1 m PMMA: 11-2211-10 1 m PC 2.0: 11-3531-10	1 m PMMA: 11-2216-10	1 m PC Fractal: 11-3211-10	1 m PMMA: 11-2217-10 1 m PC Fractal: 11-3347-10

End caps (aluminium and plastic)

WITH HOLE (PLASTIC)			
WHITE	BLACK	SILVER	GRAY
			
12-1691-00	12-1692-00	12-1695-00	12-1694-00
WITH HOLE (ALUMINIUM)			
WHITE	BLACK	SILVER	
			
12-1691-10	12-1692-10	12-1695-10	



www.lumines.com

