


IT'S EASY TO BE CREATIVE

Profile LED

X

Data sheet

A compact surface-mounted LED profile designed for LED strip installation in hard-to-reach areas. It is ideal for use as a decorative lighting element in furniture and interior finishes, as well as for suspended installations in architectural interiors.



Assembly methods





Watch the video








LED Profiles

Length (mm): 1000, 2020, 3000



	WHITE (LACQUERED)	BLACK (ANODIZED)	INOX (ANODIZED)	SILVER (ANODIZED)	RAW	GOLDEN (LACQUERED)
Profile colors						
1,0 m	10-0081-10	10-0082-10	10-0083-10	10-0084-10	10-0080-10	10-1726-10
2,02 m	10-0081-20	10-0082-20	10-0083-20	10-0084-20	10-0080-20	10-1726-20
3,0 m	10-0081-30	10-0082-30	10-0083-30	10-0084-30	10-0080-30	10-1726-30
LED strip width (mm)	up to 8					

Covers (PMMA)

Length (mm): 1000, 2020, 3000

TRANSPARENT	FROZEN	MILKY	MILKY FROSTED	BLACK PMMA	SLIM LENS 15
SLIM					
					
1 m PMMA: 11-2273-10	1 m PMMA: 11-2262-10	1 m PMMA: 11-2251-10	1 m PMMA: 11-2246-10	1 m PMMA: 11-2237-10	1 m PMMA: 11-2100-10

End caps (aluminum and plastic)

WITH HOLE					WITHOUT HOLE				
WHITE	BLACK	INOX	SILVER / GRAY	GOLDEN	WHITE	BLACK	INOX	SILVER / GRAY	GOLDEN
									
ALU 12-0082-10		ALU 12-0085-10		ALU 12-0082-11		ALU 12-0085-11		ABS 12-0081-00	
ABS 12-0082-00		ABS 12-0083-00		ABS 12-0084-00		ABS 12-0081-01		ABS 12-0082-01	
ABS 12-0083-00		ABS 12-0084-00		ABS 12-0085-00		ABS 12-0083-01		ABS 12-0084-01	
ABS 12-0081-00		ABS 12-0082-00		ABS 12-0083-00		ABS 12-0084-00		ABS 12-0085-00	

Accessories

	WHITE	BLACK	SILVER	GOLDEN		TRANSPARENT	BLACK
X METAL MOUNTING CLIP					CABLE Ø 5 mm HOLDER		
	13-0661-02	13-0802-02	13-0160-02	13-1066-02		14-7067-00	14-7067-02
X MINI PLASTIC MOUNTING CLIP							
	13-0071-00	13-0072-00	13-0073-00	13-0577-02			
HINGE		PENDANTS	WHITE	BLACK	SILVER		
	14-6045-00						
			14-2075-00	14-2076-00	14-2011-02		

Maximum dissipated power of LED light sources

for temperature profile	for temperature profile
55° C	65° C
14,0 W	18,0 W



www.lumines.com

