


IT'S EASY TO BE CREATIVE

Profile LED

Z

Data sheet

A recessed LED profile specifically designed for installation in very hard-to-reach areas. Its use does not require deep routing, as the profile features an exceptionally low height. It is well suited for decorative lighting applications in furniture and interior finishes.



Z

Assembly methods







Watch the video










LED Profiles

Length (mm): 1000, 2020, 3000


	WHITE (LACQUERED)	BLACK (ANODIZED)	INOX (ANODIZED)	SILVER (ANODIZED)	RAW	GOLDEN (LACQUERED)
Profile colors						
1,0 m	10-0101-10	10-0102-10	10-0103-10	10-0104-10	10-0100-10	10-1746-10
2,02 m	10-0101-20	10-0102-20	10-0103-20	10-0104-20	10-0100-20	10-1746-20
3,0 m	10-0101-30	10-0102-30	10-0103-30	10-0104-30	10-0100-30	10-1746-30
LED strip width (mm)	up to 12					

Covers (PMMA/PC)

Length (mm): 1000, 2020, 3000

TRANSPARENT	CLEAR	FROZEN	MILKY	MILKY FROSTED	OPAL	BLACK	LENS 15	LENS 30
BASIC								
								
1 m PMMA: 11-2213-10 1 m PC 2.0: 11-3533-10	1 m PC Fractal: 11-3213-10	1 m PMMA: 11-2212-10 1 m PC 2.0: 11-3532-10	1 m PMMA: 11-2211-10 1 m PC 2.0: 11-3531-10	1 m PMMA: 11-2216-10	1 m PC Fractal: 11-3211-10	1 m PMMA: 11-2217-10 1 m PC Fractal: 11-3347-10	1 m PMMA: 11-2060-10	1 m PMMA: 11-2080-10

End caps (aluminum and plastic)

WITH HOLE				
WHITE	BLACK	INOX	SILVER / GRAY	GOLDEN
				
ABS 12-0101-00	ALU 12-0102-10 ABS 12-0102-00	ABS 12-0103-00	ALU 12-0105-10 ABS lacq. 12-0000-50 ABS 12-0104-00	ABS 12-1799-00

Maximum dissipated power of LED light sources

for temperature profile 55° C	for temperature profile 65° C
15,8 W	21,0 W



www.lumines.com

