


IT'S
EASY
TO BE
CREATIVE

LED System


SFERO

Data sheet

A round polycarbonate LED profile that provides uniform 360° light distribution and aesthetically pleasing, consistent light lines. Designed for suspended (vertical or horizontal) and surface mounting, with the option of a mixed configuration (suspended + wall-mounted).





Assembly methods



SFERO

LED PC Profiles




Length (mm): 1000, 2000, 3000

	OPAL	OPAL + SFERO FLEX 2700 K	OPAL + SFERO FLEX 4000 K
Profile colors			
1 m	11-3631-10	26-0000-86	26-0000-89
2 m	11-3631-20	26-0000-87	26-0000-90
3 m	11-3631-30	26-0000-88	26-0000-91

Light source

2700 K	4000 K
SFERO FLEX	
	
5 m: 18-2001-27	5 m: 18-2001-40

End caps (aluminum)

MS1			
WITH HOLE (ALUMINUM)		WITHOUT HOLE (ALUMINUM)	
BLACK	SILVER	BLACK	SILVER
			
12-2362-10	12-2325-10	12-2362-11	12-2325-11
MS2			
WITH HOLE (ALUMINUM)		WITHOUT HOLE (ALUMINUM)	
BLACK	SILVER	BLACK	SILVER
			
12-2382-10	12-2385-10	12-2382-11	12-2385-11
MS3 (ALUMINUM)			
BLACK	SILVER		
			
14-2029-31	14-2029-32		

Accessories

SFERO MS2 METAL MOUNTING CLIP		METAL CABLE LOCK M10X1 4 MM		PENDANTS	
BLACK	SILVER	SILVER	BLACK	BLACK	SILVER
					
14-2029-24	14-2029-23	14-2029-37	14-2028-97	14-2029-34	14-2029-33



www.lumines.com

