

TEKKN1®

Data sheet / Karta produktu

TEKKN1 COVERS / KLOSZE

TRANSPARENCY*

Przepuszczalność*

TYPE OF COVER Rodzaj klosza	S10	S14	M21	M22	L32
FOR PROFILES Do profili	IKKE	ORRE, HOM, HELSE, BARDE, SELDE, UHRE, SKAGEN, MOSSO	ARRE	TVED, EGEN, HORST	NORS, HEDE
MILKY PC Mleczny PC	57%	50%	59%	58%	49%
					
	2,02 m 11-3441-20	2,02 m 11-3811-20	2,02 m 11-3421-20	2,02 m 11-3451-20	2,02 m 11-3461-20
	3 m 11-3441-30	3 m 11-3911-30	3 m 11-3421-30	3 m 11-3451-30	3 m 11-3461-30
FROZEN PC Mrożony PC	76%	74%	80%	76%	72%
					
	2,02 m 11-3442-20	2,02 m 11-3612-20	2,02 m 11-3422-20	2,02 m 11-3452-20	2,02 m 11-3462-20
	3 m 11-3442-30	3 m 11-3712-30	3 m 11-3422-30	3 m 11-3452-30	3 m 11-3462-30
TRANSPARENT PC Transparentny PC	86%	91%	92%	88%	87%
					
	2,02 m 11-3443-20	2,02 m 11-3413-20	2,02 m 11-3423-20	2,02 m 11-3453-20	2,02 m 11-3463-20
	3 m 11-3443-30	3 m 11-3513-30	3 m 11-3423-30	3 m 11-3453-30	3 m 11-3463-30

 * All tests were carried out in the Lumines photometry laboratory. Result tolerance $\pm 5\%$.

 * Wszystkie badania zostały wykonane w laboratorium fotometrii Lumines. Tolerancja wyniku $\pm 5\%$

TEKKN1®

by **LUMINES** Lighting

Designed & Engineered in Poland

www.tekni.com