Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Led Labs Lighting

Supplier's address: LED Labs Sp. z o.o., ul. Zakopiańska 2C, 30-418 Kraków Polska

Model identifier: WI-3Y12V9.6WW80HS

Type of light source:

| Lighting technology used: | LED | Non-directional or directional: | NDLS |
|-------------------------------|------|---------------------------------|----------------------------|
| Light source cap-type | wire | | |
| (or other electric interface) | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Only with specific dimmers |

Product parameters

| Parameter | | Value | Parameter | Value | | |
|---|------------------------------------|-------------------------|---|--------------|--|--|
| General product parameters: | | | | | | |
| Energy consum mode (kWh/100 up to the nearest | 0 h), rounded | 5 | Energy efficiency class | G | | |
| Useful luminous indicating if it ref in a sphere (360 cone (120º) or in (90º) | fers to the flux Dº), in a wide | 400 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 | | |
| On-mode po expressed in W | ower (P _{on}), | 4,8 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set | 80 | | |
| Outer | Height | 3 | Spectral power | See image | | |
| dimensions | Width | 10 | distribution in the | in last page | | |

| Claim of equivalent power(a)-If yes, equivalent power (W)-Chromaticity0,438 coordinates (x and y)0,398Parameters for LED and OLED light sources:R9 colour rendering index value11Survival factor1,00the lumen maintenance factor0,96 | without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | Depth | 500 | range 250 nm to 800 nm, at full-load | | | |
|--|---|--------------------------|------|---|-------|--|--|
| coordinates (x and y)0,398Parameters for LED and OLED light sources:0,398R9 colour rendering index value11Survival factor1,00 | Claim of equival | ent power ^(a) | - | , , , | - | | |
| Parameters for LED and OLED light sources:R9 colour rendering index value11Survival factor1,00 | | | | Chromaticity | 0,438 | | |
| R9 colour rendering index value11Survival factor1,00 | | | | | 0,398 | | |
| | Parameters for LED and OLED light sources: | | | | | | |
| the lumen maintenance factor 0,96 | R9 colour rende | ring index value | 11 | Survival factor | 1,00 | | |
| | the lumen main | tenance factor | 0,96 | | | | |

(a)'-' : not applicable;

(b)'-' : not applicable;

