

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LUMINES Lighting

**Supplier's address:** -

**Model identifier:** LUM-ILEDOS180-4K

## Type of light source:

|   |                |                                 |     |
|---|----------------|---------------------------------|-----|
| Lighting technology used:                           | LED            | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | terminal block |                                 |     |
| Mains or non-mains:                                 | MLS            | Connected light source (CLS):   | Nie |
| Colour-tuneable light source:                       | Nie            | Envelope:                       | -   |
| High luminance light source:                        | Nie            |                                 |     |
| Anti-glare shield:                                  | Nie            | Dimmable:                       | No  |

## Product parameters

| Parameter  | Value                     | Parameter  | Value                              |
|--|---------------------------|--|------------------------------------|
| <b>General product parameters:</b>   |                           |  |                                    |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 56                        | Energy efficiency class  | F                                  |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 4 670 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 900                              |
| On-mode power ( $P_{on}$ ), expressed in W   | 56,0                      | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00                               |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 83                                 |
| Outer dimensions without   | Height                    | 1 813  | Spectral power distribution in the |
|  | Width                     | 30   |                                    |
|  | Depth                     | 43   |                                    |
|  |                           |  | See image in last page             |

|   |      |  |                                      |  |
|---|------|--|--------------------------------------|--|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)                       |      |  | range 250 nm to 800 nm, at full-load |  |
| Claim of equivalent power <sup>(a)</sup>  | -    | If yes, equivalent power (W)                                       | -                                    |  |
|   |      | Chromaticity coordinates (x and y)                                 | 0,386<br>0,382                       |  |
| <b>Parameters for directional light sources:</b>  |      |  |                                      |  |
| Peak luminous intensity (cd)  | 418  | Beam angle in degrees, or the range of beam angles that can be set | 99                                   |  |
| <b>Parameters for LED and OLED light sources:</b>   |      |  |                                      |  |
| R9 colour rendering index value   | 11   | Survival factor  | 1,00                                 |  |
| the lumen maintenance factor  | 0,96 |  |                                      |  |
| <b>Parameters for LED and OLED mains light sources:</b>   |      |  |                                      |  |
| displacement factor (cos $\phi_1$ )   | 0,97 | Colour consistency in McAdam ellipses                              | 4                                    |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W)                                  | -                                    |  |
| Flicker metric (Pst LM)   | 0,0  | Stroboscopic effect metric (SVM)                                   | 0,3                                  |  |

(a) : not applicable;

(b) : not applicable;

mW/m<sup>2</sup>/nm

